



**LEGEND:**  
 (A) ITEMS FURNISHED & INSTALLED BY GC  
 (B) ITEMS FURNISHED BY OWNER, INSTALLED BY GC  
 (C) ITEMS FURNISHED & INSTALLED BY OWNER

MARK	DESCRIPTION
(A1)	REFRIGERATOR - BEVERAGE-AIR R849HC-1S
(A2)	FREEZER - BEVERAGE-AIR HF1W-1S
(A3)	GAS RANGE - MONOGRAM ZGP384LDN5S (LP)
(A5)	WARMING DRAWER - VULCAN VW2S
(A6)	UNDERCOUNTER ICE MAKER - SCOTSMAN CUS90A-1
(A7)	DISHWASHER - HOBART LX6H-2
(A8)	MICROWAVE - AMANA HD212
(A9)	MOTORIZED CEILING MOUNTED PROJECTION SCREEN - DA-LITE DESCENDER PRO #29799LS, WIDE FORMAT, 113" DIAGONAL, 87" X 96" V.A.
(A10)	4" H. X 8" W. MARKER BOARD - CLARIDGE SERIES "S", LCS II, 2" MAP RAIL W/ CORK INSERT, FLAT TRAY W END CAPS
(A11)	CEILING MOUNTED PROJECTOR - BENQ HT2055A
(A12)	CISCO 705 WEBEX BOARD
(A13)	U-LINE H-7825 LECTERN
(A14)	U-LINE H-6279MAH FOLDING TRAINING TABLE
(A15)	VAROOM 23"W. X 18" H. DESKTOP PRIVACY PANEL - FROSTED ACRYLIC
(A16)	DEHUMIDIFIER - SEE MECHANICAL DRAWINGS
(A17)	WASHER - WHIRLPOOL WFW8620H0 WHITE
(A18)	DRYER - WHIRLPOOL WED856HC, WHI PROVIDE VENTING KIT
(A19)	STACKED WASHER/DRYER COMBO - A17 & STACKED USING STACKING KIT #98984S
(A20)	WASHER/DRAWER UNIT - MAC SP045N2M
(A21)	DRYING CABINET - REAR LOCK PPE-EDC2
(A22)	ARM CHAIR - STAPLES KELTERNE LUKURA - BLACK, MODEL #50899-CC
(A23)	AIR COMPRESSOR - SIMPSON HUSKY MODEL # C33H 30 GAL. 1/2" HOSE COMMERCIAL HOSE AND WALL MOUNTED HOSE REEL EMERGENCY EYE WASH - SEE PLUMBING FIXTURE SCHEDULE
(A24)	ICE MACHINE WITH REMOTE COMPRESSOR - SCOTSMAN CUS90A-1 CLIBER, B303S BIN, ERC111-1 REMOTE CONDENSER, RTE 75 LINE SET, AP1-P FILTER
(A27)	SCBA DECON UNIT - MEIKO FV130.2 SANITIZING WASHER
(A28)	HOSE REEL - LIBERTY GARDEN #709, TAN POWDER COAT, WALL MOUNTED
(C1)	AIR COMPRESSOR
(C2)	FILL STATION
(C3)	AIR STORAGE

**EQUIPMENT SCHEDULE** E10

ITEM	DESCRIPTION
GB36	GRAB BAR 36"
GB42	GRAB BAR 42"
GBS	GRAB BAR - SHOWER
HS	STAINLESS STEEL HOOK STRIP
MBH	MOP AND BROOM HOLDER
MIR	MIRROR
PTD	PAPER TOWEL DISPENSER
RH	ROBE HOOK
SD	SOAP DISPENSER
SC	SHOWER CURTAIN
SCR	SHOWER ROD
TB	TOWEL BAR
TPD	TOILET PAPER DISPENSER

**TOILET ACCESSORIES SCHEDULE** D10

ITEM	DESCRIPTION
GB36	GRAB BAR 36"
GB42	GRAB BAR 42"
GBS	GRAB BAR - SHOWER
HS	STAINLESS STEEL HOOK STRIP
MBH	MOP AND BROOM HOLDER
MIR	MIRROR
PTD	PAPER TOWEL DISPENSER
RH	ROBE HOOK
SD	SOAP DISPENSER
SC	SHOWER CURTAIN
SCR	SHOWER ROD
TB	TOWEL BAR
TPD	TOILET PAPER DISPENSER

WALL TYPE CODES	PLAN SECTION	DESCRIPTION	FIRE RATED WALLS		ACOUSTIC WALLS	
			RATING	DTL	STC	DESIGN REFERENCE
1.		3-5/8" METAL STUDS @ 16" OC WITH 5/8" GYPSUM BOARD ON EACH SIDE				
2.		3-5/8" METAL STUDS @ 16" OC WITH 5/8" GYPSUM BOARD ON EACH SIDE	SMOKE	K10		
3.		3-5/8" METAL STUDS @ 16" OC WITH 5/8" GYPSUM BOARD ON EACH SIDE AND 3-1/2" BLANKET INSULATION			49	SA-870717
4.		3-5/8" METAL STUDS @ 16" OC WITH 5/8" GYPSUM BOARD ON EACH SIDE AND 3-1/2" BLANKET INSULATION	SMOKE	K10		
5.		8" CMU				
6.		8" CMU WITH CORE-FILL INSULATION				
7.		8" CMU WITH CORE-FILL INSULATION	1 HOUR	H13	50	TL-88-356
8.		8" CMU WITH 5/8" GYPSUM BOARD ON 7/8" METAL FURRING (16" OC) ON ONE SIDE				
9.		8" CMU WITH 5/8" GYPSUM BOARD ON 7/8" METAL FURRING (16" OC) ON ONE SIDE & CORE-FILL INSULATION	1 HOUR	H13		
10.		8" CMU WITH 5/8" GYPSUM BOARD ON 7/8" METAL FURRING (16" OC) ON ONE SIDE & CORE-FILL INSULATION	1/2 HOUR	D13		
11.		8" METAL STUDS @ 16" OC WITH 5/8" GYPSUM BOARD ON EACH SIDE AND 3-1/2" BLANKET INSULATION				
12.		6" METAL STUDS @ 16" OC WITH 5/8" GYPSUM BOARD ON EACH SIDE AND 3-1/2" BLANKET INSULATION	SMOKE	K10		
13.		8" CMU WITH CORE-FILL INSULATION	1 HOUR	D10	50	TL-88-356
14.		3-5/8" METAL STUDS @ 16" OC WITH 5/8" GYPSUM BOARD ON EACH SIDE AND 3-1/2" BLANKET INSULATION	1/2 HOUR	A10		
15.		6" METAL STUDS @ 16" OC WITH 5/8" GYPSUM BOARD ON EACH SIDE AND 3-1/2" BLANKET INSULATION	1/2 HOUR	A10		

**WALL SYMBOL CODE (SEE FLOOR PLAN):**  
 NUMBER INDICATES WALL TYPE. SEE WALL TYPE CODES IN TABLE.  
 LETTER INDICATES WALL HEIGHT. SEE WALL HEIGHT CODES.

**WALL HEIGHT CODES:**  
 A WALL EXTENDS TO 6' ABOVE FINISH CEILING. STUDS MAY EXTEND TO DECK ABOVE OR BE GRACED AS REQUIRED, AT CONTRACTOR'S OPTION.  
 B WALL EXTENDS TO FULL HEIGHT OF DECK ABOVE.  
 C WALL HEIGHT IS X'-X"

**WALL SCHEDULE NOTES:**  
 A. WALLS WITHOUT WALL TAGS ARE TO BE CONSTRUCTED BASED ON WALL CODE 1A, TYPICAL.  
 B. THE FOLLOWING INTERIOR WALL FINISH SUBSTRATES ARE TO BE PROVIDED IN LIEU OF GYPSUM BOARD (IN LIKE THICKNESSES):  
 • MOISTURE RESISTANT GYPSUM BOARD ON FIXTURE SIDE OF ALL PLUMBING WALLS  
 • CERAMITIOUS TILE BACKER BOARD ON SIDE OF WALLS SCHEDULED TO RECEIVE CERAMIC TILE  
 • ABUSE RESISTANT GYPSUM BOARD WHERE INDICATED ON FLOOR PLAN  
 C. REFERENCES HEREIN TO FIRE RATINGS APPLY ONLY TO WALLS GRAPHICALLY DESIGNATED IN PLAN TO BE FIRE RATED IN ACCORDANCE WITH THE "WALL LEGEND."  
 D. WALL TYPE INDICATED SHALL CONTINUE OVER DOOR OPENINGS AND OVER/BELOW GLAZED OPENINGS OR WINDOWS AS REQ'D. COORDINATE WITH FRAME DETAILS.

**WALL SCHEDULE NOTES (CONTINUED):**  
 E. WALL TYPES LISTED HEREIN WITH AN STC RATING ARE CONSIDERED TO BE "ACOUSTIC WALLS."  
 F. STC RATINGS INDICATED HEREIN ARE DERIVED FROM THE LABORATORY TEST INDICATED IN THE "DESIGN REFERENCE" COLUMN. TEST SOURCES ARE AS FOLLOWS:  
 USG, SA, BBN: UNITED STATES GYPSUM  
 NSC: NATIONAL GYPSUM COMPANY  
 KAL: KODARAS ACOUSTICAL LABS  
 TL: ETL-SEMKO  
 G. CONSTRUCT ACOUSTIC WALLS TO COMPLY WITH THE FOLLOWING REQUIREMENTS:  
 1. FILL ALL WALL PENETRATIONS W/ BATT INSULATION AND SEAL W/ ACOUSTICAL SEALANT.  
 2. STAGGER ELECTRICAL BOXES A MINIMUM OF 16".  
 3. APPLY ACOUSTICAL SEALANT AT PERIMETER OF STUD WALLS.  
 4. GYPSUM BOARD FASTENERS MUST NOT CONTACT MASONRY ON CMU WALLS HAVING GYP BD ON FURRING STRIPS.  
 H. PROVIDE 20 GA. STUDS AT SHOWER STALL PARTITIONS

**INTERIOR WALL TYPE SCHEDULE** C1

WALL TYPE CODE	DESCRIPTION
1.	3-5/8" METAL STUDS @ 16" OC WITH 5/8" GYPSUM BOARD ON EACH SIDE
2.	3-5/8" METAL STUDS @ 16" OC WITH 5/8" GYPSUM BOARD ON EACH SIDE
3.	3-5/8" METAL STUDS @ 16" OC WITH 5/8" GYPSUM BOARD ON EACH SIDE AND 3-1/2" BLANKET INSULATION
4.	3-5/8" METAL STUDS @ 16" OC WITH 5/8" GYPSUM BOARD ON EACH SIDE AND 3-1/2" BLANKET INSULATION
5.	8" CMU
6.	8" CMU WITH CORE-FILL INSULATION
7.	8" CMU WITH CORE-FILL INSULATION
8.	8" CMU WITH 5/8" GYPSUM BOARD ON 7/8" METAL FURRING (16" OC) ON ONE SIDE
9.	8" CMU WITH 5/8" GYPSUM BOARD ON 7/8" METAL FURRING (16" OC) ON ONE SIDE & CORE-FILL INSULATION
10.	8" CMU WITH 5/8" GYPSUM BOARD ON 7/8" METAL FURRING (16" OC) ON ONE SIDE & CORE-FILL INSULATION
11.	8" METAL STUDS @ 16" OC WITH 5/8" GYPSUM BOARD ON EACH SIDE AND 3-1/2" BLANKET INSULATION
12.	6" METAL STUDS @ 16" OC WITH 5/8" GYPSUM BOARD ON EACH SIDE AND 3-1/2" BLANKET INSULATION
13.	8" CMU WITH CORE-FILL INSULATION
14.	3-5/8" METAL STUDS @ 16" OC WITH 5/8" GYPSUM BOARD ON EACH SIDE AND 3-1/2" BLANKET INSULATION
15.	6" METAL STUDS @ 16" OC WITH 5/8" GYPSUM BOARD ON EACH SIDE AND 3-1/2" BLANKET INSULATION

**INTERIOR WALL LEGEND:**  
 NEW STUD WALLS  
 NEW CMU WALLS  
 FURRING, AS SCHEDULED

**EXTERIOR WALLS:**  
 REFER TO WALL SECTIONS

THE FOLLOWING DESIGNATION, WHEN INCLUDED WITHIN NEW WALLS, GRAPHICALLY INDICATE FIRE RATED WALLS WITH RATINGS AS LISTED BELOW:  
 --- 1 HR FIRE RATING  
 --- SMOKE BARRIER

**GENERAL DIMENSIONING NOTES** A1

A. DIMENSIONS LOCATING NEW EXTERIOR MASONRY WALLS ARE TO EXTERIOR FACE OF MASONRY UNLESS NOTED OTHERWISE.  
 B. DIMENSIONS LOCATING NEW EXTERIOR STUD WALLS ARE TO EXTERIOR FACE OF STUDS.  
 C. DIMENSIONS LOCATING NEW INTERIOR MASONRY WALLS ARE TO FACE OF MASONRY.  
 D. DIMENSIONS LOCATING NEW INTERIOR STUD WALLS ARE TO FINISHED WALL SURFACES.  
 E. IF THE LOCATION OF ANY BUILDING ELEMENT IS NOT OBVIOUS OR CANNOT BE DETERMINED BY DIMENSION, MATHEMATICS, OR AS NOTED ABOVE, CONTACT THE ARCHITECT PRIOR TO LOCATING THE ELEMENT.

**FleischmanGarcia**  
 ARCHITECTURE • INTERIOR DESIGN  
 24 HYDRA PARK AVENUE, SUITE 100  
 FORT WORTH, TEXAS 76102  
 PHONE (817) 728-8800  
 FAX (817) 728-8800  
 REGISTRATION NUMBER: AA 000021

**Pasco County Fire & Rescue Station No. 17**  
 New Port Richey, Florida

**FGA PROJECT NUMBER**  
 19039

**ISSUE DATE**  
 05-25-20

**REVISIONS:**  
 DATE: -  
 DATE: -  
 DATE: -

**SHEET NUMBER**  
 A2.6